

## **SPECIFICATION Silhouette Window Shadings**

Supply of **Silhouette Window Shadings from HunterDouglas** in 3" vane size having headrail and bottom rail made of aluminium alloy extruded profile, powder coated and provided in standard natural white color. The rolling tube should be made up of aluminium alloy from extruded profile of Ø34 mm. The headrail dimensions should be in the range of : H 58 mm x 72 mm or 62 mm x 81 mm for the larger headrail. The cassette should conceal the working mechanism rotary-clutch that raises, lowers and tilts the shade contains and protects shading fabric when fully raised. All plastic parts are colour co-ordinated. Operation options: endless cord with cordweight colour coordinated or 24 V DC built in tubular motor. Installation to be done by quick release brackets (wall or ceiling). The fabric of this Silhouette Window Shadings should be of 100% woven anti static polyester vanes which have facings between 2 sheer layers (50 mm wide) to reduce glare. Sheer layers made of white 100% knit polyester & the selection of colors, textures and opacities from the HunterDouglas® collection rests with customer choice. The shading to be operated by Easyrise mechanism with a continuous cord loop operating option. **The FABRIC shall be constructed from spun-bonded 100% polyester fibre, having Greenguard certified and recommended for sensitive areas like clean room condition and laboratories.**