

SPECIFICATION

Supply of **Vertical Blinds from HunterDouglas** having 100mm fabric SLATS with with standard overlap of not less than 3/8" and stacking 7/32" apart. Groovers extruded from PVC with .030" maximum thickness with 1/8" clear lip to accept inserts of all available commercial fabrics. Fabric to be flame retardant fiberglass (Aberdeen FR) or polyester (Cumulus FR, Caldwell FR). (Empress V 36% fiberglass, 64% PVC, 5% openness). 1/2" wide heattreated extruded aluminum, dip coated with baked polyester coating and Finish with manufacturer's standard colors selected.CHANNEL: Standard type measuring 1 3/4" x

1 5/16" x .045" thick constructed of painted ivory aluminum.Internally fit with .24" diameter heavy-duty extruded aluminum tilt rod, engineered thermal plastic carrier trucks,end caps and components required for specified performance

and designed for smooth, quiet, trouble free operation. CARRIER TRUCKS:

Engineered thermal plastic 7/16"

thick and 1 5/8" wide with wheels and worm-and-spur gears to ensure rotation with perfect alignment and synchronization.

Solid molded engineered thermal plastic asymmetrical carrier stems provide ease of louver installation and removal. Wheelless

lead carrier moves along elongated bearing surface. SPACER LINKS:

Stainless steel 5/16" X .008" spacer

links smoothly space and stabilize carrier trucks.TRAVERSING: Stretch resistant, non-fraying, and lint free

lock knit polyester cord provide traversing capabilities for side,

center, and off-center draws.MOUNTING HARDWARE: Manufacturer's standard

L-bracket with clip (outside mounts) & clip only (inside mounts) provide required support.

.